

**! SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

**Name of product** AT-44 Multi-Oil  
Code-Nr. 152500

**1.2. Relevant identified uses of the substance or mixture and uses advised against****Recommended intended purpose(s)**

Technical Liquids

**1.3. Details of the supplier of the safety data sheet****Distributor**

WEICON GmbH & Co. KG  
Königsberger Str. 255, DE-48157 Münster  
Phone : +49(0)251 / 9322 - 0, Fax : +49(0)251 / 9322 - 244  
E-Mail : msds@weicon.de  
Internet : www.weicon.de

**Advice**

Produktsicherheit / Product-Safety-Department  
Phone : +49(0)251 / 9322 - 0  
Fax : +49(0)251 / 9322 - 244  
E-mail (competent person):  
msds@weicon.de

**1.4. Emergency telephone number**

EMERGENCY CONTACT - UK, UAE, South Africa (24h): Tel:  
++44 1865 407333 (English)  
TRANSPORT EMERGENCY CONTACT - UK, UAE, South  
Africa (24h): Tel: ++44 1865 407333 (English)

**Manufacturer**

WEICON GmbH & Co. KG  
Königsberger Str. 255, DE-48157 Münster

**1.4. Emergency telephone number**

GIFTNOTRUF/TRANSPORTNOTRUF - Deutschland (24h):  
Tel: ++49 69 222 25285 (Deutsch, Englisch)

**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture****Classification according to Regulation (EC) No 1272/2008 [CLP/GHS]**

Hazard classes and Hazard categories	Hazard Statements	Classification procedure
--------------------------------------	-------------------	--------------------------

Flam. Liq. 3	H226	
STOT SE 3	H336	
Asp. Tox. 1	H304	

**Hazard Statements**

H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H336	May cause drowsiness or dizziness.

**2.2. Label elements****Labelling according to Regulation (EC) No 1272/2008 [CLP/GHS]**

GHS02



GHS07



GHS08

**Signal word**

Danger

**Hazard Statements**

H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H336	May cause drowsiness or dizziness.

**Precautionary Statements**

P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233	Keep container tightly closed.
P243	Take precautionary measures against static discharge.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P271	Use only outdoors or in a well-ventilated area.
P301 + P310	IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
P303 + P361 + P353	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P312	Call a POISON CENTER or doctor/physician if you feel unwell.
P331	Do NOT induce vomiting.
P370 + P378	In case of fire: Use foam for extinction.
P403 + P233	Store in a well-ventilated place. Keep container tightly closed.
P403 + P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.
P501	Dispose of contents/container to hazardous or special waste collection point.

**Hazardous ingredients for labeling**

Distillates (petroleum), hydrotreated light, Naphtha (petroleum), hydrotreated heavy

**Supplemental Hazard information (EU)**

Repeated exposure may cause skin dryness or cracking.

**2.3. Other hazards****Results of PBT and vPvB assessment**

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

**! SECTION 3: Composition/ information on ingredients****3.1. Substances**

not applicable

**3.2. Mixtures**



Safety Data Sheet according to Regulation (EC)  
No. 1907/2006 (REACH)

Printed 05.08.2019  
revision 13.07.2018 (GB) Version 8.7

**AT-44 Multi-Oil**

**Description**

Mixture of oils, solvents and additives

**! Hazardous ingredients**

CAS No	EC No	Name	[% weight]	Classification according to Regulation (EC) No 1272/2008 [CLP/GHS]
95-63-6	202-436-9	1,2,4-trimethylbenzene	0,1 < 1	Flam. Liq. 3, H226 / Acute Tox. 4, H332 / Eye Irrit. 2, H319 / STOT SE 3, H335 / Skin Irrit. 2, H315 / Aquatic Chronic 2, H411
64742-47-8	920-107-4	Hydrocarbons, C12-C15, n-alkanes, isoalkanes < 2% aromatics	25 < 50	Asp. Tox. 1, H304
64742-48-9	919-857-5	Naphtha (petroleum), hydrotreated heavy	10 < 25	Flam. Liq. 3, H226 / Asp. Tox. 1, H304 / STOT SE 3, H336 /

**REACH**

CAS No	Name	REACH registration number
95-63-6	1,2,4-trimethylbenzene	01-2119472135-42
64742-47-8	Hydrocarbons, C12-C15, n-alkanes, isoalkanes < 2% aromatics	01-2119453414-43
64742-48-9	Naphtha (petroleum), hydrotreated heavy	01-2119463258-33

**SECTION 4: First aid measures**

**4.1. Description of first aid measures**

**General information**

Remove contaminated soaked clothing immediately.

**In case of inhalation**

Remove the casualty into fresh air and keep him immobile.

In the event of symptoms refer for medical treatment.

**In case of skin contact**

In case of contact with skin wash off with soap and water.

Consult a doctor if skin irritation persists.

**In case of eye contact**

In case of contact with eyes rinse with plenty of water carefully. In the event of persistent symptoms seek medical treatment.

**In case of ingestion**

If swallowed or in case of vomiting, danger of infiltration into the lungs (danger of aspiration).

Do not induce vomiting.

Call for a doctor immediately.

**4.2. Most important symptoms and effects, both acute and delayed**

**Physician's information / possible symptoms**

Shortness of breath

Headache

Confusion

**4.3. Indication of any immediate medical attention and special treatment needed**

**Treatment (Advice to doctor)**

If swallowed or in the event of vomiting, risk of entering the lungs.

---

**! SECTION 5: Firefighting measures****5.1. Extinguishing media****Suitable extinguishing media**

Alcohol-resistant foam

Dry powder

Carbon dioxide

Water spray jet

**! Unsuitable extinguishing media**

Full water jet

**5.2. Special hazards arising from the substance or mixture**

In case of fire formation of dangerous gases possible.

**5.3. Advice for firefighters****Special protective equipment for fire-fighters**

Fire-fighting operations, rescue and clearing work under effect of combustion and smoulder gases just may be done with breathing apparatus.

**Additional information**

Cool endangered containers with water spray jet.

---

**! SECTION 6: Accidental release measures****6.1. Personal precautions, protective equipment and emergency procedures****For non-emergency personnel**

Ensure adequate ventilation.

Use personal protective clothing.

Keep away sources of ignition.

High risk of slipping due to leakage/spillage of product.

**6.2. Environmental precautions**

Inform pollution control authorities if product gets into the sewerage systems or open waters.

Do not discharge into the drains or bodies of water..

Do not discharge into the drains/surface waters/groundwater.

**6.3. Methods and material for containment and cleaning up**

Take up with absorbent material (e.g. sand, kieselguhr, acid binder, general-purpose binder, sawdust).

After taking up the material dispose according to regulation.

**6.4. Reference to other sections**

Safe handling: see section 7

Disposal: see section 13

Personal protection equipment: see section 8

---

**! SECTION 7: Handling and storage****7.1. Precautions for safe handling****! Advice on safe handling**

Avoid formation of aerosols.

Care for thoroughly room ventilation, if necessary use in well ventilated area with local exhaust ventilation at workplace.

**General protective measures**

Avoid contact with eyes and skin

Do not inhale gases/vapours/aerosols.

**AT-44 Multi-Oil****Hygiene measures**

At work do not eat, drink and smoke.

Wash hands before breaks and after work.

**Advice on protection against fire and explosion**

Keep away from sources of ignition - No smoking

The product is combustible.

Take precautionary measures against static discharges.

**7.2. Conditions for safe storage, including any incompatibilities****Requirements for storage rooms and vessels**

Keep in closed original container.

**Advice on storage compatibility**

Do not store together with animal feedstuffs.

Do not store together with food.

**Further information on storage conditions**

Protect from direct solar radiation.

Storage temperature may not exceed 50°C (=122°F).

Store container at cool and aired place.

Store in a dry place.

**7.3. Specific end use(s)****Recommendation(s) for intended use**

See section 1.2

**! SECTION 8: Exposure controls/personal protection****8.1. Control parameters****! Ingredients with occupational exposure limits to be monitored**

CAS No	Name	Code	[mg/m3]	[ppm]	Remark
	Oil Mist	8 hours	5		
		Short-term	10		

**Indicative occupational exposure limit values (91/322/EEC, 2000/39/EC, 2006/15/EC or 2009/161/EU)**

CAS No	Name	Code	[mg/m3]	[ppm]	Remark
95-63-6	1,2,4-trimethylbenzene	8 hours	100	20	

**DNEL-/PNEC-values****DNEL worker**

CAS No	Substance name	Value	Code	Remark
64742-48-9	Naphtha (petroleum), hydrotreated heavy	871 mg/m3	DNEL long-term inhalative (systemic)	
		208 mg/kg bw/day	DNEL long-term dermal (systemic)	

**DNEL Consumer**

CAS No	Substance name	Value	Code	Remark
64742-48-9	Naphtha (petroleum), hydrotreated heavy	185 mg/m3	DNEL long-term inhalative (systemic)	
		125 mg/kg bw/day	DNEL long-term dermal (systemic)	
		125 mg/kg bw/day	DNEL long-term oral (repeated)	

**Additional advice**

The statutory local and national regulations have to be observed.

**8.2. Exposure controls****Respiratory protection**

Filter A or environment-independent breathing apparatus

In case of insufficient ventilation or long-term effect use breathing apparatus.

**Hand protection**

In the cases of special applications, it is recommended to check the chemical resistance with the manufacturer of the gloves.

In the cases of special applications, it is recommended to check the chemical resistance with the manufacturer of the gloves.

Glove material specification [make/type, thickness, permeation time/life, wetting resistance]: Nitrile rubber; 0,4mm; 480min;60min.

**Eye protection**

tightly fitting goggles

**Other protection measures**

protective clothing

**Appropriate engineering controls**

Care for thoroughly room ventilation, if necessary use in well ventilated area with local exhaust ventilation at workplace.

**SECTION 9: Physical and chemical properties****9.1. Information on basic physical and chemical properties****Appearance**

liquid

**Colour**

grey

**Odour**

solvent-like

**Odour threshold**

not determined

**Important health, safety and environmental information**

	Value	Temperature	at	Method	Remark
<b>pH value</b>	not determined				
<b>boiling range</b>	162 °C				
<b>Melting point / Freezing point</b>	not determined				
<b>Flash point</b>	36 °C				
<b>Vapourisation rate</b>	not determined				
<b>Flammable (solid)</b>	not applicable				
<b>Flammability (gas)</b>	not applicable				
<b>Ignition temperature</b>	> 200 °C				
<b>Self ignition temperature</b>					The product is not self-igniting.
<b>Lower explosion limit</b>	0,5 Vol-%				



## Safety Data Sheet according to Regulation (EC)

No. 1907/2006 (REACH)

Printed 05.08.2019

revision 13.07.2018 (GB) Version 8.7

**AT-44 Multi-Oil**

	Value	Temperature	at	Method	Remark
<b>Upper explosion limit</b>	7 Vol-%				
<b>Vapour pressure</b>	1 hPa	20 °C			
<b>Relative density</b>	0,89 g/cm <sup>3</sup>	20 °C			
<b>Vapour density</b>	not determined				
<b>Solubility in water</b>					No or low immiscibility
<b>Solubility/other</b>	not determined				
<b>Partition coefficient n-octanol/water (log P O/W)</b>	not determined				
<b>Decomposition temperature</b>	not determined				
<b>Viscosity dynamic</b>	not determined				
<b>Viscosity kinematic</b>	not determined				
<b>Solvent content</b>	48,7 %				
<b>Solids content</b>	9,8 %				
<b>Oxidising properties</b>	No information available.				
<b>Explosive properties</b>	The product is considered non-explosive ; nevertheless explosive vapour/air mixtures can be generated .				
<b>9.2. Other information</b>	No information available.				

**! SECTION 10: Stability and reactivity****10.1. Reactivity**

No information available.

**10.2. Chemical stability**

No information available.

**10.3. Possibility of hazardous reactions**

No hazardous reactions known.

**10.4. Conditions to avoid**

Keep away from heat.

**10.5. Incompatible materials**

No information available.

**10.6. Hazardous decomposition products**

**Thermal decomposition**

Remark No decomposition if used as directed.

**! SECTION 11: Toxicological information****11.1. Information on toxicological effects****Acute toxicity/Irritation/Sensitization**

	Value/Validation	Species	Method	Remark
<b>LD50 acute oral</b>	> 5000 mg/kg	rat		CAS: 64742-47-6
<b>LD50 acute dermal</b>	> 5000 mg/kg	rabbit		CAS: 64742-47-6
<b>LC50 acute inhalation</b>	4951 mg/m3 (4 h)	rat		CAS: 64742-48-9
<b>Skin irritation</b>	low irritant effect - not necessary to label			
<b>Eye irritation</b>	non-irritant			
<b>Skin sensitization</b>	non-sensitizing			

**Subacute Toxicity - Carcinogenicity**

	Value	Species	Method	Validation
<b>Mutagenicity</b>				No experimental information on genotoxicity in vivo available.
<b>Reproduction-Toxicity</b>				No indications of toxic effects were observed in reproduction studies in animals.
<b>Carcinogenicity</b>				No indications of carcinogenic effects are available from long-term trials.

**Specific target organ toxicity (single exposure)**

May cause drowsiness or dizziness.

**Aspiration hazard**

May be fatal if swallowed and enters airways.

**Experiences made from practice**

Often and long skin contact may cause degreasing and desiccation of the skin which may cause skin irritation.

**! Additional information**

The product is to be handled with the caution usual with chemicals.

Other hazardous properties may not be excluded.

The product has not been tested. The information is derived from the properties of the individual components.





## SECTION 12: Ecological information

### 12.1. Toxicity

#### Ecotoxicological effects

	Value	Species	Method	Validation
<b>Fish</b>	LL0 1000 mg/l (96 h)	Oncorhynchus mykiss		CAS: 64742-47-6
<b>Daphnia</b>	EL0 1000 mg/l (48 h)	Daphnia magna		CAS: 64742-47-6
<b>Algae</b>	NOELR 100 mg/l (72 h)	Pseudokirchneriella subcapitata		CAS: 64742-48-9

### 12.2. Persistence and degradability

No information available.

### 12.3. Bioaccumulative potential

The product has not been tested. Because of the product's consistency and low solubility in water bioavailability is not likely.

### 12.4. Mobility in soil

No information available.

### 12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

### 12.6. Other adverse effects

#### General regulation

Even in the event of low quantities penetration into the underground drinking water is contaminated.

Do not allow uncontrolled leakage of product into the environment.

Product is not allowed to be discharged into the ground water or aquatic environment.

Product is not allowed to be discharged into aquatic environment, drains or sewage treatment plants.

The ecotoxic effect of the product has not been tested. The information on this is given on the basis of details in the literature.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

#### Waste code No.

07 01 04\*

20 01 13\*

#### Name of waste

other organic solvents, washing liquids and mother liquors

Solvents

Wastes marked with an asterisk are considered to be hazardous waste pursuant to Directive 2008/98/EC on hazardous waste.

#### Recommendations for the product

Remove in accordance with local official regulations.

#### Recommendations for packaging

Dispose of according to the local waste regulations.

#### General information

Assignment to a waste code number / waste identification according to the EWC is to be carried out on a sector or process-specific basis.

**SECTION 14: Transport information**

	<b>ADR/RID</b>	<b>IMDG</b>	<b>IATA-DGR</b>
<b>14.1. UN number</b>	1993	1993	1993
<b>14.2. UN proper shipping name</b>	FLAMMABLE LIQUID, N.O.S. (Naphtha (petroleum), hydrotreated heavy (NOTA P))	FLAMMABLE LIQUID, N.O.S. (Naphtha (petroleum), hydrotreated heavy)	Flammable liquid, n.o.s. (Naphtha (petroleum), hydrotreated heavy)
<b>14.3. Transport hazard class(es)</b>	3	3	3
<b>14.4. Packing group</b>	III	III	III
<b>14.5. Environmental hazards</b>	No	No	No

**14.6. Special precautions for user**

No information available.

**14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

not applicable

**Land and inland navigation transport ADR/RID**

Hazard label(s) 3

tunnel restriction code D/E

Special provisions 640E

Classification code F1

**! SECTION 15: Regulatory information****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****VOC standard****VOC content** 48,66 %**VOC value** 433,5 g/L**15.2. Chemical Safety Assessment**

Chemical safety assessments for substances in this mixture were not carried out.

**! SECTION 16: Other information****! Recommended uses and restrictions**

National and local regulations concerning chemicals shall be observed.

For industrial use only.

**Further information**

Each user is responsible for the implementation of the national special regulations.

The information contained herein is based on the state of our knowledge. It characterizes the product with regard to the appropriate safety precautions. It does not represent a guarantee of the properties of the product.

Please observe the following disclaimer! --- Our safety data sheets have been compiled according to effective EU-directives, WITHOUT taking into account the special national directives concerning the handling of hazardous substances.

Danish MAL Code 5-3

Indication of changes: "!" = Data changed compared with the previous version. Previous version: 8.6

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.



Safety Data Sheet according to Regulation (EC)

No. 1907/2006 (REACH)

Printed 05.08.2019

revision 13.07.2018 (GB) Version 8.7

**AT-44 Multi-Oil**

---

- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H411 Toxic to aquatic life with long lasting effects.